



RAM® Docks for Honeywell CT40/CT45/CT47

AVAILABLE SKUS



CLICK OR SCAN
TO VIEW ALL PRODUCTS



Docks

RAM-HOL-HON12U

Non-Powered

RAM-HOL-HON12PU

Powered

RAM-HOL-HON12PLU

Powered, Locking

RAM-HOL-HON12PDU

Powered, Single USB Type-A

RAM-HOL-HON12PDLU

Powered, Single USB Type-A, Locking

Docks w/ Heated Pogo Pins

RAM-HOL-HON12PHU

Powered, Heated

RAM-HOL-HON12PDHU

Powered, Single USB Type-A, Heated

RAM-HOL-HON12PHLU

Powered, Heated, Locking

RAM-HOL-HON12PDHLU

Powered, Single USB Type-A, Heated, Locking

PRIMARY MARKETS



RETAIL



WAREHOUSE & MANUFACTURING



FIELD SERVICE



LAST MILE DELIVERY

Patented & Pats Pend.

rammount.com/ip



RAM® Docks for Honeywell CT40/CT45/CT47

FEATURES & BENEFITS

Patented & Pats Pend.
rammount.com/ip



Pogo Pin Charging

Protect the charge port and increase efficiency by utilizing the device's pogo pad docking contacts—simply dock the Honeywell CT40, CT45, CT47 to keep the device charged and connected to supported USB Type-A peripherals. All powered RAM® docks come equipped with pogo pin technology to enable a seamless docking experience.



Heated Pogo Pins

Heating elements provide the necessary heat required to prevent pogo pins from locking up in cold temperatures.



Form-Fit Docking

This RAM® holder is spring-loaded, making it easy for one-handed docking and removal. Each dock comes with optional press-in inserts to enable docking of the Honeywell CT40, CT45, CT47 without the OEM boot.



Mount It

With RAM® Compatibility™, customize your mount specific to your environment. Choose from thousands of mounting options to achieve the optimal workflow with your Honeywell CT40, CT45, CT47 device.



RAM® Docks for Honeywell CT40/CT45/CT47

SPECIFICATIONS

Patented & Pats Pend.
rammount.com/ip



DIMENSIONS

7.83" (H) x 3.7" (W) x 3.17" (D)
19.8 cm (H) x 9.39 cm (W) x 8.05 cm (D)

HARDWIRE POWER SUPPLIES

RAM-GDS-CHARGE-M55-V7B1U
RAM-GDS-CHARGE-M55-V8BU

CERTIFICATIONS

CE, UKCA, RoHS, WEEE

INPUT VOLTAGE

5VDC

POWER CONNECTOR TYPE

5.5mm DC Connector Female

POWER CABLE LENGTH

1 Meter

PERIPHERAL POWER OUTPUT

900mA @ 5VDC (1x USB-A)

DATA CONNECTOR TYPE

USB Type-A Female

DATA CABLE LENGTH

1 Meter





RAM® Docks for Honeywell CT40/CT45/CT47

COMPATIBLE MOUNTS

Patented & Pats Pend.
rammount.com/ip

Static & Light Duty Mounting



RAM-138U

RAM® Double Ball Mount with Diamond Plate Adapter C-Size with Standard Arm



RAM-B-404-238

RAM® Tough-Claw™ Medium Clamp Mount with Diamond Plate B-Size with Standard Arm

Forklift & Heavy Duty Mounting



RAM-102U-247

RAM® Universal Post Clamp Mount with Diamond Plate C-Size with Standard Arm



RAM-102U-B-247

RAM® Universal Post Clamp Mount with Diamond Plate C-Size with Short Arm

Alternate Bases



RAP-365-224-1U

RAM® Twist-Lock™ Triple Suction Cup Ball Base C Size



RAM-235-1U

RAM® Double U-Bolt Ball Base for 1.25" - 1.5" Rails C Size



RAM-271U-2

RAM® Rail Clamp Ball Base for 2" - 2.5" Rails C Size



RAM-202-225-2U

RAM® Drill-Down Dashboard Ball Base with Backing Plate C Size