



RAM® Docks for Zebra TC22 / TC27

AVAILABLE SKUS



CLICK OR SCAN
TO VIEW ALL PRODUCTS



Docks

RAM-HOL-ZE24U

Non-powered

RAM-HOL-ZE24LU

Non-powered, Key-Locking

RAM-HOL-ZE24PU

Powered

RAM-HOL-ZE24PLU

Powered, Key-Locking

RAM-HOL-ZE24-1U

Non-powered, with inserts

RAM-HOL-ZE24L-1U

Non-powered, Key-Locking, with inserts

RAM-HOL-ZE24P-1U

Powered, with inserts

RAM-HOL-ZE24PL-1U

Powered, Key-Locking, with inserts

Power Supplies

RAM-GDS-CHARGE-V7B1U

GDS® 10-30V Hardwire Charger with Female USB Type A Connector

RAM-GDS-CHARGE-V8BU

GDS® 30-64V Hardwire Charger with Female USB Type A Connector

PRIMARY MARKETS



RETAIL



WAREHOUSE & MANUFACTURING



FIELD SERVICE

Patented
rammount.com/ip



RAM® Docks for Zebra TC22 / TC27

FEATURES



Pogo Pin Charging

Protect the charge port and increase efficiency by utilizing the device's pogo pad docking contacts — simply dock the TC22/TC27 to keep the device charged. Each powered RAM® dock comes equipped with pogo pin technology for this seamless docking experience.



Stylus Holder

Integrated snap-in stylus holder on all docks prevent lost or dangling styluses when on-the-go.



Removable Inserts

("-1U" Part Numbers Only)

Part numbers ending in "-1U" indicate docks that include removable inserts. When installed, these inserts retain form-fit docking of the TC22/TC27 when the rugged boot is removed from the device.



Mount It

With RAM® Compatibility™ customize your mount to your environment. Our recommended mount is the RAM-101U Drill-Down mount.

Patented
rammount.com/ip






RAM® Docks for Zebra TC22 / TC27

SPECIFICATIONS

Patented
rammount.com/ip



SPECIFICATIONS

DIMENSIONS

7.72" (H) x 3.66"(W) x 2.54"(D)
19.6cm(H) x 9.29cm(W) x 6.45cm(D)

HARDWARE POWER SUPPLIES

RAM-GDS-CHARGE-V7B1U
RAM-GDS-CHARGE-V8BU

CERTIFICATIONS

CE, UKCA, WEEE, RoHS

INPUT VOLTAGE

4.5-5.4VDC

POWER CONNECTOR TYPE

USB Type-A Female

POWER CABLE LENGTH

1.25 Meter



RAM® Docks for Zebra TC22 / TC27

COMPATIBLE MOUNTS

Patented & Pats Pend.
rammount.com/ip

Retail



RAM® Double Ball Drill-Down Mount
RAM-B-138U



RAM® Platform Double Ball Mount
RAP-B-291-A-238U



RAM® Tough-Claw™ Small Clamp Mount
RAP-B-400-238U



RAM® Tough-Mag™ 66mm Dia. Mount
RAM-B-MAG66U
RAM-B-103-238U

Field Service



RAM® Double Ball Drill-Down Mount
RAM-B-138U



RAM® Tough-Claw™ Small Clamp Mount
RAP-B-400-238U



RAM® Twist-Lock™ Suction Cup Mount
RAM-B-166U



RAM® Pod HD™ Mount w/ 12" Aluminum Rod
RAM-316-HD-238U

Material Handling



RAM® Square Post Mount 1.75"-4" Wide
RAM-B-247U
RAM-B-103-238U



RAM® Tough-Claw™ Small Clamp Mount
RAP-B-400-238U